

AD-A081 169

SCHOOL OF AEROSPACE MEDICINE BROOKS AFB TX

F/G 6/19

MEASURING RIGHT VENTRICULAR PRESSURE IN CONSCIOUS 6-STRESSED MI--ETC(U)

DEC 79 J E WHINNERY, M H LAUGHLIN, E F JONES


UNCLASSIFIED SAM-TR-79-39

NL

1 OF 1
AD
A081169



END
DATE
FILMED
3-80
DDC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

Report SAM-TR-79-39

2
b s
LEVEL

ADA 081 169

MEASURING RIGHT VENTRICULAR PRESSURE IN CONSCIOUS G-STRESSED MINIATURE SWINE

James E. Whinnery, Major, USAF, MC, FS
M. Harold Laughlin, Captain, USAF, BSC
Earl F. Jones, Major, USAF, VC

DTIC
ELECTE
FEB 27 1980
S D C

DDC FILE COPY

December 1979

Final Report for Period 1 January 1979 - 30 June 1979

Approved for public release; distribution unlimited.

USAF SCHOOL OF AEROSPACE MEDICINE
Aerospace Medical Division (AFSC)
Brooks Air Force Base, Texas 78235



80 2 26 021

NOTICES


This final report was submitted by personnel of the Biodynamics Branch, Crew Technology Division, and Surgical Support Branch, Veterinary Sciences Division, USAF School of Aerospace Medicine, Aerospace Medical Division, AFSC, Brooks Air Force Base, Texas, under job order 7930-12-21.


When U.S. Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.


The animals involved in this study were procured, maintained, and used in accordance with the Animal Welfare Act of 1970 and the "Guide for the Care and Use of Laboratory Animals" prepared by the Institute of Laboratory Animal Resources - National Research Council.

This report has been reviewed by the Office of Public Affairs (PA) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication.


JAMES E. WHINNERY, Major, USAF, MC, FS
Project Scientist


SIDNEY D. LEVERETT, JR., Ph.D.
Supervisor


LAWRENCE J. ENDERS
Colonel, USAF, MC
Commander

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER SAM-TR-79-39	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) MEASURING RIGHT VENTRICULAR PRESSURE IN CONSCIOUS G-STRESSED MINIATURE SWINE	5. TYPE OF REPORT & PERIOD COVERED Final Report 1 Jan 79 - 30 Jun 79	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) James E. Whinnery, Major, USAF, MC, FS M. Harold Laughlin, Captain, USAF, BSC Earl F. Jones, Major, USAF, VC	8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS USAF School of Aerospace Medicine (VNB and VSS) Aerospace Medical Division (AFSC) Brooks AFB, Texas 78235	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62202F 7938-12-21	
11. CONTROLLING OFFICE NAME AND ADDRESS USAF School of Aerospace Medicine (VNB and VSS) Aerospace Medical Division (AFSC) Brooks AFB, Texas 78235	12. REPORT DATE December 1979	13. NUMBER OF PAGES 5
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) 12/8	15. SECURITY CLASS. (of this report) UNCLASSIFIED	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Millar pressure transducer Miniature conscious G-stressed swine Right ventricular pressure Venous access		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A surgical technique was developed, for conscious miniature swine, which allowed a Millar pressure transducer to be passed through a permanently placed catheter in the cranial vena cava via the external jugular vein. The recordings of central venous, right atrial, and right ventricular pressures were easily obtainable in fully conscious ambulatory animals. Our experience with this technique demonstrated that these pressure measurements could be monitored even when the animal was subjected to severe stress, such as +10G _z to -6G _z , on a centrifuge, having the capability of continuous data collection.		

DD FORM 1 JAN 73 1473

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

317000

JF

REPORT DOCUMENTATION PAGE	
1. AGENCY USE ONLY (Leave blank)	
2. AUTHOR	
3. TITLE	
4. AUTHORING ORGANIZATION NAME(S) AND ADDRESS(ES)	
5. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)	
6. AUTHORING ORGANIZATION REPORT NUMBER	
7. AUTHORING ORGANIZATION REPORT DATE	
8. PERFORMING ORGANIZATION REPORT DATE	
9. PERFORMING ORGANIZATION REPORT NUMBER	
10. PROGRAM ELEMENT NAME(S)	
11. PROGRAM ELEMENT NUMBER	
12. PROGRAM ELEMENT DATE	
13. PROGRAM ELEMENT NUMBER	
14. PROGRAM ELEMENT DATE	
15. PROGRAM ELEMENT NUMBER	
16. PROGRAM ELEMENT DATE	
17. PROGRAM ELEMENT NUMBER	
18. PROGRAM ELEMENT DATE	
19. PROGRAM ELEMENT NUMBER	
20. PROGRAM ELEMENT DATE	
21. PROGRAM ELEMENT NUMBER	
22. PROGRAM ELEMENT DATE	
23. PROGRAM ELEMENT NUMBER	
24. PROGRAM ELEMENT DATE	
25. PROGRAM ELEMENT NUMBER	
26. PROGRAM ELEMENT DATE	
27. PROGRAM ELEMENT NUMBER	
28. PROGRAM ELEMENT DATE	
29. PROGRAM ELEMENT NUMBER	
30. PROGRAM ELEMENT DATE	
31. PROGRAM ELEMENT NUMBER	
32. PROGRAM ELEMENT DATE	
33. PROGRAM ELEMENT NUMBER	
34. PROGRAM ELEMENT DATE	
35. PROGRAM ELEMENT NUMBER	
36. PROGRAM ELEMENT DATE	
37. PROGRAM ELEMENT NUMBER	
38. PROGRAM ELEMENT DATE	
39. PROGRAM ELEMENT NUMBER	
40. PROGRAM ELEMENT DATE	
41. PROGRAM ELEMENT NUMBER	
42. PROGRAM ELEMENT DATE	
43. PROGRAM ELEMENT NUMBER	
44. PROGRAM ELEMENT DATE	
45. PROGRAM ELEMENT NUMBER	
46. PROGRAM ELEMENT DATE	
47. PROGRAM ELEMENT NUMBER	
48. PROGRAM ELEMENT DATE	
49. PROGRAM ELEMENT NUMBER	
50. PROGRAM ELEMENT DATE	
51. PROGRAM ELEMENT NUMBER	
52. PROGRAM ELEMENT DATE	
53. PROGRAM ELEMENT NUMBER	
54. PROGRAM ELEMENT DATE	
55. PROGRAM ELEMENT NUMBER	
56. PROGRAM ELEMENT DATE	
57. PROGRAM ELEMENT NUMBER	
58. PROGRAM ELEMENT DATE	
59. PROGRAM ELEMENT NUMBER	
60. PROGRAM ELEMENT DATE	
61. PROGRAM ELEMENT NUMBER	
62. PROGRAM ELEMENT DATE	
63. PROGRAM ELEMENT NUMBER	
64. PROGRAM ELEMENT DATE	
65. PROGRAM ELEMENT NUMBER	
66. PROGRAM ELEMENT DATE	
67. PROGRAM ELEMENT NUMBER	
68. PROGRAM ELEMENT DATE	
69. PROGRAM ELEMENT NUMBER	
70. PROGRAM ELEMENT DATE	
71. PROGRAM ELEMENT NUMBER	
72. PROGRAM ELEMENT DATE	
73. PROGRAM ELEMENT NUMBER	
74. PROGRAM ELEMENT DATE	
75. PROGRAM ELEMENT NUMBER	
76. PROGRAM ELEMENT DATE	
77. PROGRAM ELEMENT NUMBER	
78. PROGRAM ELEMENT DATE	
79. PROGRAM ELEMENT NUMBER	
80. PROGRAM ELEMENT DATE	
81. PROGRAM ELEMENT NUMBER	
82. PROGRAM ELEMENT DATE	
83. PROGRAM ELEMENT NUMBER	
84. PROGRAM ELEMENT DATE	
85. PROGRAM ELEMENT NUMBER	
86. PROGRAM ELEMENT DATE	
87. PROGRAM ELEMENT NUMBER	
88. PROGRAM ELEMENT DATE	
89. PROGRAM ELEMENT NUMBER	
90. PROGRAM ELEMENT DATE	
91. PROGRAM ELEMENT NUMBER	
92. PROGRAM ELEMENT DATE	
93. PROGRAM ELEMENT NUMBER	
94. PROGRAM ELEMENT DATE	
95. PROGRAM ELEMENT NUMBER	
96. PROGRAM ELEMENT DATE	
97. PROGRAM ELEMENT NUMBER	
98. PROGRAM ELEMENT DATE	
99. PROGRAM ELEMENT NUMBER	
100. PROGRAM ELEMENT DATE	

MEASURING RIGHT VENTRICULAR PRESSURE IN CONSCIOUS G-STRESSED MINIATURE SWINE

INTRODUCTION

The swine has become very useful in many areas of biomedical research (1,2). In the specific area of acceleration research, the miniature swine is particularly important as a human model because of several similarities to man: (a) similar coronary vasculature; (b) similar heart-to-eye distance; (c) similar tolerances to $+G_z$ acceleration; and (d) the ability to perform spontaneous straining maneuvers analogous to those used by aviators to maintain vision and consciousness while pulling high $+G_z$ during aerial combat maneuvers. This animal, therefore, provides an excellent model for invasive investigation of the stressful and possibly hazardous effects of head-to-foot ($+G_z$) acceleration. The application of the results of these studies should thus afford maximum protection to aircrewmembers exposed to high $+G_z$ in the future.

A specific drawback in using miniature swine for biomedical research is the lack of an easily obtainable vascular access. In this animal, the posterior pinna veins of the ears constitute the only venous access normally used for catheterization. Others have described diverse methods for insertion and long-term implantation (3) of catheters for blood sampling and injections. We have had similar success in long-term (60 - 90 days) maintenance of patent Silastic rubber catheters for similar purposes, including injection of radioactive microspheres.

We are currently investigating the effects of $+G_z$ acceleration stress on cardiac (4) and pulmonary function (5). A desirable part of this effort was to measure right ventricular pressures in conscious miniature swine during $+G_z$ stress. Due to the possible effects of thoracic surgery on pulmonary mechanics and function, we devised a technique which would allow these measurements, in conscious animals, and not require thoracic surgical manipulation.

→ This report presents a technique which allows the introduction of a Millar pressure transducer (~~Catheter DC 350, 5 Fr~~)^{1/} into the right cardiac chambers, via a chronically implanted venous catheter, in conscious animals. The transducer can then be secured, and pressures in the right ventricle can be measured in conscious animals during exposure to various stressful environments. Since neither analgesia nor anesthesia is needed before, during, or after transducer placement, measurements can be made in (fully) unanesthetized animals. K

^{1/} Millar Instruments, Inc., P.O. Box 18227, Houston, TX 77023.

MATERIALS AND METHODS

Surgical Procedures

The miniature swine utilized in acceleration research at the USAF School of Aerospace Medicine are a Pitman-Moore strain.^{2/} All animals are maintained under veterinary supervision, in individual runs, at all times. Surgical techniques similar to those previously reported (3) are used for insertion of the implanted catheters. All procedures were carried out using sterile techniques. Dow Corning Silastic medical grade rubber tubing (o.d. 3.18 mm, and i.d. 1.58 mm)^{3/} was implanted for blood withdrawal or selective injection. At the same implantation site, a larger polyethylene catheter (o.d. 3.49 mm, and i.d. 2.67 mm)^{4/} was also inserted, for subsequent introduction of the pressure transducer (Figs. 1 and 2). With the pig lying on its right side, the topographic landmark for the skin incision is a straight line between the mandibular angle of the jaw and the point of the shoulder. The dissection is continued deeper in a straight ventral (straight down) direction, so that the external jugular vein may be located and isolated. The vein was ligated cranially with 2-0 silk, and a second 2-0 ligature silk was passed twice around the caudal end to control retrograde hemorrhage. After a small longitudinal incision was made in the vein, the catheters were introduced and advanced to the point that the tips would be in the desired location (cranial vena cava). The second silk ligature was then tied, snugly enough to prevent bleeding, around the catheters without compressing or occluding them. A third silk ligature was similarly placed a short distance from the second one; then these two ligatures were used to anchor the two catheters to the vein and prevent their expulsion. This anchoring was accomplished by tying a short loop into the ligature, passing each free end around one catheter from opposite directions, and then tying snugly without occluding the catheter. After each tie around a catheter, its patency was determined by aspirating with a heparinized-saline-filled syringe, a three-way stopcock, and a blunt needle attached to the end of each catheter. A gauze sponge was then wrapped around each catheter, the catheters were cross-clamped lightly near the neck, and the syringes and needles were removed.

By digital palpation, the edges of the lateral processes of the cervical vertebrae could be identified, and the catheter ends could be tunneled through the subcutaneous tissue just lateral to the vertebrae and exteriorized on the dorsum of the neck. This procedure was accomplished by means of a large, straight, stainless-steel needle with a double loop of umbilical tape tied through the eye. The end of the catheter, which was placed through the loop and doubled over, could be pulled to the dorsum of the neck. Changes in direction of the catheters were kept to gentle curves rather than sharp angular turns. Finally, the syringes were reattached, and the catheter patency rechecked. After closure of the lateral neck incision, the catheters were flushed, filled with straight heparin, and stoppered with sterile metal plugs.

^{2/} Vita Vet Laboratories, Inc., Box 587, Marion, IN 46952.

^{3/} Dow Corning, Medical Products Div., P.O. Box 1592, Midland, MI 48640.

^{4/} Becton, Dickinson and Company, Rutherford, NJ 07070.




Figure 1. Surgical placement of chronically implanted Silastic and polyethylene catheters into the miniature swine vasculature.




Figure 2. Placement of the Millar pressure transducer through the polyethylene catheter into the right ventricle of the miniature swine for measurement of right ventricular pressures.

Catheter patency was maintained by daily--or every other day--flushing (withdrawal first) with normal saline, and then leaving the catheter filled with heparin before replacing the end metal catheter plug. Flushing may be done while the pig is standing free in a crate, or by closely confining the animal in a corner of its run by means of a plywood hurdle board. With either method, little resistance is usually met in the flushing procedure.

Millar Transducer Placement

The animal is restrained but completely awake, and rarely struggles during transducer placement. For measuring central venous and right heart pressures, a 5 French PC-350 Millar catheter (o.d. 1.67 mm) was calibrated and then carefully introduced into the large polyethylene catheter. After the Millar pressure transducer was inserted 4-5 cm into the catheter, a thin coat of sterile glycerin was applied to the remainder of the transducer shaft to decrease friction and allow easy in-and-out movement of the transducer. The transducer was advanced until a characteristic atrial pressure trace was obtained, then the transducer shaft was moved in and out and simultaneously rotated in an attempt to pass through the tricuspid valve. In our experience, a 10-min period is usually enough for successful placement of the transducer in the right ventricle. When the transducer was in the desired location, the polyethylene tubing was tied snugly to the transducer shaft with umbilical tape to prevent blood loss caused by increased pressure development as a result of grunting during stress. After withdrawal of the transducer, the catheter should be completely flushed with saline and filled with heparin, and the sterile closure pin then inserted. Both catheters can be used at the same time: one, for pressure measurements; the other, for withdrawal or injection.

RESULTS AND DISCUSSION

Our results with respect to maintaining Silastic catheter patency are in agreement with those of others (3), since we frequently were able to keep catheters patent as long as 60 - 90 days with frequent flushing. Neither systemic nor local infections have been a problem when sterile flushing techniques are followed. The animal is apparently completely undisturbed by the catheters placed on the dorsum of the neck. Being able successfully to measure central venous, right atrial, and right ventricular pressures repeatedly in fully conscious animals during stress is very advantageous--especially when a conscious physiologic model, not recently under the influence of pharmacologic agents, is needed.

Our animals were subjected to head-to-foot $+G_z$ acceleration stress up to $+10G_z$, and foot-to-head $-G_z$ acceleration stress to $-6G_z$, without loss or reduction in pressure signal output. During the $+G_z$ stress, the animal performs a vigorous straining maneuver and, in addition, is physically compressed into the formfitted fiberglass couch in which it rides on the centrifuge. This process represents considerable movement without loss of continual data collection. The method would be specifically useful in measuring right-sided pressures during other types of stress, such as treadmill testing, when a non-violated thoracic cavity is desired.

REFERENCES

1. Burton, R. R. Positive (+G_z) acceleration tolerances of the miniature swine: Application as a human analog. Aerospace Med 44:294-298 (1973).
2. Douglas, W. R. Of pigs and men and research: A review of applications and analogies of the pig, sus scrofa, in human medical research. Space Life Sciences 3:226-234 (1972).
3. Christison, G. I., and T. M. Curtin. A simple venous catheter for sequential blood sampling from unrestrained pigs. Lab Animal Care 19:259-262 (1969).
4. Whinnery, J. E., et al. Lung perfusion imaging in the miniature swine at zero and +7G_z. J Am Vet Rad Soc 20:33-38 (1979).
5. Laughlin, M. H., W. M. Witt, and R. N. Whittaker, Jr. The effects of high sustained +G_z on regional coronary blood flow in adult miniature swine. ASMA Preprints 83-84. Aerospace Medical Assoc., Annual Scientific Meeting, New Orleans, La., May 8-11, 1978.

Accession For	
NTIS GRA&I	
DDC TAB	
Unannounced	
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or special
A	